



celplast
metallized products



CERAMIS® CPP-005

SILICON OXIDE-COATED POLYPROPYLENE FILM

Typical Values

CPP-005 is a SiO_x-coated polypropylene film with clear transparent appearance and superior barrier properties.

Properties	Typical Value	Units	Test Method
Yield	61,17	m ² /kg	
Thickness	0.70 18	Mil µm	
Tensile Strength	238 MD 230 TD	N/mm ²	ASTM D882
Elongation at break	170 MD 30 TD	%	ASTM D882
Haze	1.6	%	ASTM D1003-92
Static COF	0.65 SiO _x /SiO _x 0.80 oPP/oPP	-	DIN ISO8295
WVTR	<0.10	g/m ² /24 hr.	ASTM F1249-90 (73.4° F, 85% RH) Laminated to 3mil CPP
OTR	<0.10	cc/m ² /24 hr.	ASTM D-3985 (73.4° F, 50% RH) Laminated to 3mil CPP

This product is in compliance with the regulation FDA 21 CFR 177.1520 (c) (1.1) and (3.1). When laminated to an approved substrate, the laminate is compliant with the requirements of EU directive 2002/72/EC.

The information and opinions herein are believed to be true and accurate and presented without guarantee or responsibility on our part. No recommendation for use of our product is intended as a patent infringement. No warranty of any kind with respect to patents held by others is implied or intended.

Mar 2013