



celplast
metallized products



CERAMIS® CPA-001

SILICON OXIDE-COATED NYLON FILM

Typical Values

CPA-001 is a SiOx -coated Nylon film with a combination of excellent clarity and outstanding barrier properties. It is ideally suited for non-retort pouch and lidding applications.

Properties	Typical Value	Units	Test Method
Yield	58,16	m ² /kg	
Thickness	0.60 15	Mil µm	
Tensile Strength	251.66 MD 251.66 TD	N/mm ²	ASTM D 882
Elongation at break	125 MD 125 TD	%	ASTM D 882
Haze	3.0	%	ASTM D1003-92
Static COF	0.70 SiOx/SiOx 0.40 oPA/oPA	-	DIN ISO8295
OTR	0.020	cc/m ² /24 hr.	ASTM D-3985 (73.4° F, 50% RH) Laminated CPA-001/3.6mil cPP

This product is in compliance with the regulation FDA 21 CFR 177.1500. When laminated to an approved substrate, the laminate is compliant with the requirements of EU directive 2002/72/EC.

The information and opinions herein are believed to be true and accurate and presented without guarantee or responsibility on our part. No recommendation for use of our product is intended as a patent infringement. No warranty of any kind with respect to patents held by others is implied or intended.

Mar 2013