

CERAMIS[®] Ultra CPP-009
SILICON OXIDE-COATED (SiOx)
POLYPROPYLENE FILM



Developmental Data Sheet
SiOx One Side, Heat Sealable Other Side

CPP-009 is a SiOx-coated polypropylene film with clear transparent appearance and exceptional barrier performance. SiOx coated on one side and heat sealable on the other side, although not recommended as primary sealant.

Shelf life of six months in the original packaging.

Application: non-retort transparent high barrier packaging applications.

Properties	Typical Value		Units	Test Method
Yield	61,30		m ² /kg	
Thickness	0,70 18		Mil µm	
Tensile Strength	MD TD	100 220	N/mm ²	ISO 527-1-2 (Test speed 100%/min; 23°C, 50% rh)
Elongation at break	MD TD	160 60	%	ISO 527-1-2 (Test speed 100%/min; 23°C, 50% rh)
Haze	5,0		%	ASTM D1003-92
Coefficient of friction (dynamic)	0,60 <0,40		SiOx/SiOx oPP/oPP	DIN EN ISO 8295
WVTR	<0,10		g/(m ² d)	ASTM F1249-90 (73.4° F, 85% RH) CPP009/adhesive solvent based/2.8mi cPP
OTR	<0,10		cm ³ /(m ² bar d)	ASTM F1927-07 (73.4° F, 50% RH) CPP009/adhesive solvent based/2.8mi cPP

This product is in compliance with the regulation FDA 21 CFR 177.1630. When laminated to an approved substrate, the laminate is compliant with the requirements of EU directive 2002/72/EC.

The information and opinions herein are believed to be true and accurate and presented without guarantee or responsibility on our part. No recommendation for use of our product is intended as a patent infringement. No warranty of any kind with respect to patents held by others is implied or intended.