



**celplast**  
metallized products



**CERAMIS® CPP-008**  
**SILICON OXIDE-COATED (SiOx)**  
**POLYPROPYLENE FILM**  
**Developmental Data Sheet**  
SiOx One Side, Heat Sealable Other Side

CPP-008 is a SiOx-coated polypropylene film with clear transparent appearance and moderate barrier properties. SiOx coated on one side and heat sealable on the other side.

Properties	Typical Value		Units	Test Method
Yield	61,00		m <sup>2</sup> /kg	
Thickness	0,70 18		Mil µm	
Tensile Strength	140 280	MD TD	N/mm <sup>2</sup>	ASTM D882
Elongation at break	220 60	MD TD	%	ASTM D882
Haze	5,0		%	ASTM D1003-92
Coefficient of friction (dynamic)	0,60 <0,50	SiOx/SiOx oPP/oPP	-	DIN EN ISO 8295
WVTR	0,2		g/(m <sup>2</sup> d)	ASTM F1249-90 (73.4° F, 85% RH) CPP008/adhesive solvent based/2.8mi cPP
OTR	5		cm <sup>3</sup> /(m <sup>2</sup> bar d)	ASTM D-3985-2005 (73.4° F, 50% RH) CPP008/adhesive solvent based/2.8mi cPP

This product is in compliance with the regulation FDA 21 CFR 177.1630. When laminated to an approved substrate, the laminate is compliant with the requirements of EU directive 2002/72/EC.

The information and opinions herein are believed to be true and accurate and presented without guarantee or responsibility on our part. No recommendation for use of our product is intended as a patent infringement. No warranty of any kind with respect to patents held by others is implied or intended.