



celplast
metallized products



CERAMIS® CPP-009 **SILICON OXIDE-COATED (SiOx)** **POLYPROPYLENE FILM**

Developmental Data Sheet SiOx One Side, Heat Sealable Other Side

CPP-009 is a SiOx-coated polypropylene film with clear transparent appearance and exceptional barrier performance. SiOx coated on one side and heat sealable on the other side.

Properties	Typical Value		Units	Test Method
Yield	49,50		m ² /kg	
Thickness	0,88 22		Mil µm	
Tensile Strength	150 300	MD TD	N/mm ²	ISO 527-1-2 (Test speed 100%/min; 23°C, 50% rh)
Elongation at break	160 60	MD TD	%	ISO 527-1-2 (Test speed 100%/min; 23°C, 50% rh)
Haze	6,0		%	ASTM D1003-92
Coefficient of friction (dynamic)	0,70 <0,40	SiOx/SiOx oPP/oPP	-	DIN EN ISO 8295
WVTR	<0,15		g/(m ² d)	ASTM F1249-90 (73.4° F, 85% RH) CPP009/adhesive solvent based/2.8mi cPP
OTR	<0,1		cm ³ /(m ² bar d)	ASTM F1927-07 (73.4° F, 50% RH) CPP009/adhesive solvent based/2.8mi cPP

This product is in compliance with the regulation FDA 21 CFR 177.1630. When laminated to an approved substrate, the laminate is compliant with the requirements of EU directive 2002/72/EC.

The information and opinions herein are believed to be true and accurate and presented without guarantee or responsibility on our part. No recommendation for use of our product is intended as a patent infringement. No warranty of any kind with respect to patents held by others is implied or intended.